




# BPOWER 015 AGM 50Ah 540A

Excellent AGM series batteries are characterized by a very long service life and cyclic durability which is many times higher than in other starter batteries. The main feature of the AGM technology is the use of special separators made of a glass mat soaked in electrolyte. AGM batteries are completely sealed and maintenance-free, so they can also work inside vehicles without the risk of leakage. AGM technology guarantees the highest resistance to start-ups and partial recharges, thanks to which they are successfully used in most vehicles with the Start & Stop system and the energy recovery system.

BASIC PARAMETERS		TECHNOLOGY	
Nominal voltage (V)	12	Technology	Ca/Ca VRLA
Nominal capacity 20HR (Ah)	50	Performance marking	W5-C2-V3-M3
Cold cranking perform. (EN -18°C)	540	Separator	AGM
Recom. charging current	5A	Flame Arrestor	✓
PHYSICAL PARAMETERS		CASE FEATURES	
Dimensions (L x W x H)	207 x 175 x 190 mm	Case type	L1 DIN AGM
Weight (kg)	15,00	Hold down	B3
Terminal type	T1	Handles	✓
Case material	Polipropylen PP	End venting	✓
		Cell assembly layout	0
		Lid type	VRLA


## Terminal type

T1




## Cell assembly layout

0



## Battery hold down

B3



**Headquarters in Warsaw**  
Jana Kazimierza 61  
01-267 Warszawa

**Branch in Gdansk**  
Twarda 12  
80-871 Gdańsk

+48 22 877 54 96  
biuro@baterie.com.pl  
www.baterie.com.pl

**BP BATERIE**  
PRZEMYSŁOWE