


BPOWER GTX7A 6Ah 110A




Sealed, maintenance-free, factory-started batteries made using GEL technology. They are used in newer generation motorcycles and in all quads, jet skis and snowmobiles. SUPREME series batteries meet the most demanding customer expectations regarding failure-free operation even in the most difficult conditions. Apart from checking the voltage at the poles, no additional checks are required. They are characterized by high starting currents, which additionally affects the comfort of use. They meet the most demanding safety standards.

| BASIC PARAMETERS | | TECHNOLOGY | |
|---------------------------|------------------|-----------------------------------|---------------|
| Nominal voltage (V) | 12 | Technology | CA/CA |
| Nominal capacity C10 (Ah) | 6 | Separator | AGM |
| Cold cranking amperage | 110 | | |
| PHYSICAL PARAMETERS | | CHARGING PARAMETERS (25°C) | |
| Dimensions (L x W x H) | 150 x 87 x 93 mm | Charging voltage | 14,0V - 14,4V |
| Weight (kg) | 2,60 | Recommended max. charging current | 0.6A |
| Terminal type | 5 | | |


Terminal type



Cell layout



Dimensions



Headquarters in Warsaw
Jana Kazimierza 61
01-267 Warszawa

Branch in Gdansk
Twarda 12
80-871 Gdańsk

+48 22 877 54 96
biuro@baterie.com.pl
www.baterie.com.pl

BP BATERIE
PRZEMYSŁOWE