


## **BPOWER YTX20L-BS 18**Ah **270**A

BPOWER PLATINUM series batteries are sealed and maintenance-free batteries made using AGM technology. They are used in newer generation motorcycles and in all quads, jet skis and snowmobiles. In order to maintain factory freshness, the batteries are available in a dry version with electrolyte included. Start-up takes place shortly before the battery is installed. A tightly closed battery, once filled with electrolyte, becomes completely maintenance-free.

BASIC PARAMETERS		TECHNOLOGY	
Nominal voltage (V)	12	Technology	CA/CA
Nominal capacity C10 (Ah)	18	Separator	AGM
Cold cranking amperage	270		
PHYSICAL PARAMETERS		CHARGING PARAMETERS (2	5°C)
PHYSICAL PARAMETERS Dimensions (L x W x H)	175 x 87 x 155 mm	CHARGING PARAMETERS (2) Charging voltage	5°C) 14,0V - 14,4V
	175 x 87 x 155 mm 6,17		

## Terminal type





16.2 Side view




Top view

## Dimensions






Cell layout



0



**Headquarters in Warsaw** Jana Kazimierza 61 01-267 Warszawa **Branch in Gdansk** Twarda 12 80-871 Gdańsk

+48 22 877 54 96 biuro@baterie.com.pl www.baterie.com.pl BP BATERIE PRZEMYSŁOWE