

Yuasa Technical Data Sheet

Yuasa REC14-12 Industrial VRLA Battery



Specifications

Nominal voltage (V)	12
20-hr rate Capacity to 10.5V at 20°C (Ah)	13
10-hr rate Capacity to 10.8V at 20°C (Ah)	11.9

Dimensions

Length (mm)	151 (±1)
Width (mm)	98 (±1)
Height (mm)	94 (±2)
Height over terminals (mm)	97.5 (±2)
Mass (kg)	4.2

Terminal Type

FASTON - Quickfit / release (JST where stated)	6.35
------------------------------------------------	------

Operating Temperature Range

Storage (in fully charged condition)	-15°C to +50°C
Charge	-0°C to +40°C
Discharge	-15°C to +40°C

Storage

Capacity loss per month at 20°C (% approx.)	3
---------------------------------------------	---

Case Material

Standard	ABS (UL94:HB)
----------	---------------

Charge Voltage

Float charge voltage at 20°C (V)/Block	13.65 (±1%)
Float charge voltage at 20°C (V)/Cell	2.275 (±1%)
Float Chg voltage tmp correction factor from std 20°C (mV)	-3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block	14.52 (±3%)
Cyclic (or Boost) charge Voltage at 20°C (V)/Cell	2.42 (±3%)
Cyclic Chg voltage tmp correction factor from std 20°C (mV)	-4

Charge Current

Float charge current limit (A)	3.25
Cyclic (or Boost) charge current limit (A)	3.25

Maximum Discharge Current

1 second (A)	195
1 minute (A)	70

Cyclic Life Data

100% DOD down to 80% capacity	300
75% DOD down to 80% capacity	500
50% DOD down to 80% capacity	600
25% DOD down to 80% capacity	1400

Impedance


Measured at 1 kHz (mΩ)	10.1
------------------------	------

Design Life & Approvals

EUROBAT Classification: General Purpose	6 to 9
Yuasa design life at 20°C (yrs)	7



Layout



3rd Party Certifications

ISO9001 - Quality Management Systems
UNDERWRITERS LABORATORIES Inc.



Safety

Installation

Can be installed and operated in any orientation except permanently inverted.

Handles

Batteries must not be suspended by their handles (where fitted).

Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.

